

- Distinctive sliding door with wide stiles and rails
- Suitable for new construction or retrofit

FRAME

- 5 5/8" all PVC multi-chamber profiles
- Extruded-on nailing fin, full 4 9/16" behind fin
- Welded or mechanically fastened frame
- Anodized aluminum threshold
- Double continuous weatherstrips

SASHES

- Wide stiles & rails sash
- Colonial look of profile at the edge of the glass
- Vertical stiles reinforced by metallic stiffeners
- Sashes are designed for 1" i.g.
- Multi-point lock is standard
- High quality nylon coated ball bearing rollers
- Sashes are weeped top and bottom for reversibility
- Two-sided tape glazing system
- Compatible with mini-blinds between glass
- Interior glazing beads for easy glass replacement
- Strong interlocking at the meeting rail area

SCREEN

- Heavy-duty extruded aluminum screen
- Miter cut corner
- Four adjustable rollers
- Black fiberglass screen mesh

STANDARD DIMENSIONS

Nominal	Type	FRAME SIZE	
		Remodelling 6/8	New Construction 6/10
5/0	OX or XO	59 1/4" x 79 1/2"	58 3/4" x 81 1/8"
6/0	OX or XO	71 1/4" x 79 1/2"	70 3/4" x 81 1/8"
8/0	OX or XO	95 1/4" x 79 1/2"	94 3/4" x 81 1/8"
9/0	XOX	103 13/16" x 79 1/2"	103" x 81 1/8"
9/0	OXO	107 3/4" x 79 1/2"	106 5/16" x 81 1/8"
10/0	OXXO	116 7/8" x 79 1/2"	115 7/8" x 81 1/8"
12/0	XOX	139 13/16" x 79 1/2"	139" x 81 1/8"
12/0	OXO	143 3/4" x 79 1/2"	142 5/16" x 81 1/8"
12/0	OXXO	140 7/8" x 79 1/2"	139 7/8" x 81 1/8"

Remodelling sizes also available in 8/0 tall version at 95 1/2" high
Non-standard sizes available upon request



Jazz
SLIDING
DOOR

**DISTINCTION
& ELEGANCE**

OPTIONS

- Interior brass handle
- Key lock
- Foot lock
- Security bar
- Extension jambs
- Brick mould with aluminum sill extension

GLASS

- Clear
- Low-E
- Georgian (contoured) grids
- Other glass types available upon request

WARRANTY

- 10 years on seal failure of glass
- 20 years on PVC
- One year on operation

COLORS

- Blue White #141
- Cream White #115

PERFORMANCES

The Jazz Sliding patio door has successfully met the following standards:

- Canada: CAN / CGSB-82.1-M89
- USA: AAMA / NWWDA 101/LS 2-97
- CSA certified

	Air Infiltration	Water Resistance	Structural Resistance	Test Size
Canadian	A3	B4	C3	71 1/4" x 81 1/8"
U.S.A.	DP-50 Rated			71 1/4" x 81 1/8"

The product meets or exceeds the requirements of the energy efficiency programs. Product is qualified into the Energy Star program for specific zones. Contact our sales people for specific areas.

THERMOPLAST
A Member of the Royal Group of Companies

3035 Le Corbusier Blvd
Laval (Quebec) Canada
H7L 4C3
Tel.: (450) 687-5115
Fax: (450) 687-5196



Proud Member